MZ 3T53D


3 Megapixel
Turbo HD

KEY FEATURES


- 18fps@3M; 25fps@1080p
- Coaxial transmission for HD video and control signal
- Common 75-5 similar coaxial cable lossless transm. up to 300m
- High speed, long distance, real-time transmission
- ICR switching
- OSD accessible through recorder
- IP66
- 36pcs IR LED, 30 meter
- 2.8-12mm lens



SPECIFICATION	MZ 3T53D
Pick Up Element	1/3"CMOS 3 Mega Pixels
Number of Pixels	1920(H)×1536(V)
Horizontal Resolution	1536P
Frame rate	18fps@3M; 25fps@1080p
SYNC.	Internal
VIDEO.OUT	TVI/960H
Lens	2.8-12mm lens
IR Series Distance	Max. 30 Meter with 36pcs IR LED
Power supply	DC12V, 450mA
Minimum Illumination	0.01Lux(F1.2)
TV System	PAL/NTSC
Electric Shutter	PAL 1/50s-1/10000s,NTSC 1/60s-1/10000s
S/N Ratio	48dB(min)(AGC closed)
WDR	D-WDR OFF/ON
DNR	2D-DNR
WHITE Balance	ATW/MWB
AE MODE	GLOBE/BLC
OSD	Accessible through recorder
Coaxial	Yes
Language	English/Italian/Spanish
Day/Night	Ext Color, B/W
Transmission distance	75-5 300M
Operation Temperature	Temperature -20C+55C, Humidity less than 85%RH
Case Dimension	146(L)×134(W)×121(H)mm



DIMENSIONS



A tökéletes képminőség érdekében használjon megfelelő HD videobalun átalakítót UTP kábelezés esetében.
Ajánlott: Folksafe HDP4001 HD video balun csomag

