HD PRO

Series marked for the installer looking for a high-level camera emphasizing the difference in image quality. The Pro series cameras are suitable for indoor and outdoor applications where professional video surveillance is required.

PROVISION ISR
PROTECTING YOUR PRIVACY

DI-380A-MVF

8MP Motorized Vari-Focal Lens Large Dome/Turret Camera With IR LED

This 4K dome/turret camera presents a stunning 8-megapixel image, equipped with a 2.8-12mm motorized lens, it is designed for medium distance surveillance (up to 40m) for both indoor and outdoor scenarios. Featuring 4in1 technology selectable by a protected dipswitch the camera is ideal for Plug & Play over existing analog infrastructure.

PRO P HD

8 MP



BLC

Control over coax

3D-DNR

IR LED

2.8-12 mm Lens

IP67 Protection rating

40m IR IR View 0 Lux

4 IN 1

BUILT-IN MICROPHONE

MOTORIZED LENS

Infra Red

MAIN FEATURES

- DI-380A-MVF 8MP Motorized Vari-Focal Lens Large Dome/Turret Camera With IR LED
- Sensor: 1/2.5” 8MP CMOS Sensor
- Selectable Output: 8MP: 3840×2160 AHD/TVI/CVI 5MP: 2592×1944 AHD/TVI 4MP: 2560×1440 AHD/TVI/CVI CVBS: 700TVL
- Lens: 2.8-12mm Mega-Pixel Motorized Vari-Focal (78°-31.3°)
- True Day&Night-ICR
- 3D-DNR
- BLC
- Illumination: 40m (3 High-Power IR LED)
- IP67
- Weight: 695g
- Power: DC12V/650mA

DI-380A-MVF

PROVISION ISR
PROTECTING YOUR PRIVACY

SPECIFICATIONS

Video	
Image Sensor	1/2.5" 8MP CMOS Sensor
Image Format	8MP/4MP - 16:9, 5MP - 4:3
Effective Pixels	3864x2202
Scanning System	Progressive
Min. Illumination	Color：0.01lux @F1.2, AGC ON B/W：0lux with IR
Day & Night	True Day&Night-ICR
Day & Night Modes	Ext/Auto/Day/Night

Compression	
Resolution	8MP: 3840x2160 AHD/TVI/CVI 5MP: 2592x1944 AHD/TVI 4MP: 2560x1440 AHD/TVI/CVI CVBS: 700TVL
Frame Rate	8MP @ 12/15FPS, 5MP @ 20FPS, 4MP @ 25/30FPS, CVBS @ 25/30FPS

Image	
Backlight Compensation	BLC
S/N Ratio	≥52dB（AGC OFF）
Privacy Zone	no
Noise Reduction	3D-DNR
Image Enhancement	BLC

On Screen Data	
CoC Support	Yes
OSD Menu	Available via CoC Only

Lens	
Field of View	2.8-12mm Mega-Pixel Motorized Vari-Focal (78°-31.3°)
Iris	DC Iris
Lens Mount	Ø14 Mount

DI-380A-MVF

Connectivity	
Audio Connectivity	N/A

Housing	
Illumination	40m (3 High-Power IR LED)
Bracket	3-Axis Bracket
Protection Rate	IP67
Dimensions	Φ113*99.6mm
Weight (gross)	695g
Power	DC12V/650mA
Work Environment	-30℃ ~ 50℃，10% ~ 90% humidity

DI-380A-MVF

DIMENSIONS

