KAC Alarm Company
Limited
15-19 Trescott Road
Smallwood
Redditch
England
B98 7AH

T: +44 (0) 1527 406655
F: +44 (0) 1527 406677
E: sales@kac.co.uk
W: www.kac.co.uk

call points

door magnets

detectors

sounders strobes

pull stations

Resistor Monitored Call Point



WR2072/SR

Manual Break Glass Fire Alarm Call Points to suit all environments. Models are supplied with series monitoring resistors of 470 or 680Ohms, making them compatible with the majority of UK conventional fire panels.

Device Type	Manual Break Glass Call Point		
Installation	INDOOR	RAINPROOF	WATERPROOF
Ingress Protection	IP24D	IP55	IP67
Circuit Configuration	Normally open contacts complete with series monitoring resistor		
Resistor Ohmic Values and Wattages	470ohms 1W 680ohms 1W	470ohms 1W 680ohms 1W	470ohms 2.5W 680ohms 2.5W
Approvals	EN54-11 Certified by Loss Prevention Certification Board		
Operating Temperature Range	-30°C to +70°C		
	Order Codes		
Surface 470ohm	WR2072/SR-470	WR7/2072-470	WR4072-470
Flush 470ohm	WR2072-470	N/A	N/A
Surface 680ohm	WR2072/SR-680	WR7/2072-680	WR4072-680
Flush 680ohm	WR2072-680	N/A	N/A



WR7/2072



WR4072

E. & O.E.

Document Ref. LIT:172
March 2003