16 CH AHD + 8 CH IP Hybrid DVR

SA-16200AHD-2 (1U)

720P 1080P 1080P 3MP

AHD CVBS IP | Onvif | H.264 Compression | HDMI | PTZ

Audio | USB | Mouse | 2 HDD | Mobile

Internet Monitoring | DDNS | CMS | P2P



MODEL		SA-16200AHD-2 (1U)
System	Compression Format	High profile H.264
	ONVIF	Yes
	Format	AHD/CVBS
Video	Input	16CH AHD Standard BNC + 8CH IP (Over Network)
	Standard Output	HDMI, VGA (800x600, 1024x768, 1280x1024), CVBS
Audio	Input	4CH
	Output	1CH
	Two Way Audio	Yes
Recording – AHD	Real-Time Recording	16CH 1080P Half Real-Time
	2MP (1080P)	240FPS (NTSC)/200FPS (PAL) Total. Up to 15/12FPS Per Channel
	1MP (720P)	480FPS (NTSC)/400FPS (PAL)
Recording – Analog	Real-Time Recording	16CH 960H Real-Time
	960H	480FPS (NTSC)/400FPS (PAL)
	D1	No
	CIF	No
Recording – IP	Real-Time Recording	8CH 1080P Real-Time
	3MP	180FPS (NTSC)/150FPS (PAL) Total. Up to 30/25FPS Per Channel
	2MP (1080P)	240FPS (NTSC)/200FPS (PAL)
	1.3MP (960P)	240FPS (NTSC)/200FPS (PAL)
	1MP (720P)	240FPS (NTSC)/200FPS (PAL)
Recording – General	Recording Modes	Schedule, Manual, Motion, Sensor
Playback	AHD/CVBS Playback	8CH
	IP Playback	1CH
	Search Mode	Time, Event, File Management
Backup	USB	2 USB 2.0 Port
	DVD Burner	No
	Backup Format	AVI/DAT
Remote Application	AHD Stream	Master Stream 1-25/30FPS@720P / 1-12/15FPS@1080P; Sub-Stream: Up to 1-25FPS@720P
	Analog Stream	Master Stream 1-25/30FPS@960H; Sub-Stream Up to 1-25FPS@960H
	IP Stream	Master Stream 1-25/30FPS@1080P; Sub-Stream Up to 1-25/30FPS@D1
	Master Stream	Up to 4Ch@Recording Resolution
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)
	CMS	Yes
	Mobile Application	ProvisionCAM for iPhone/Android; ProvisionHD for iPad/Android Tablet
	User Access	10 Users Online with Professional Autorithy Management
Alarm	Input	4CH
	Output	1CH
Storage	HDD	2 SATA (4TB)
	E-SATA	No
PTZ	Connection	RS-485
	Supported Protocols	Pelco D, Pelco P, Samsung, Visca, ONVIF, CoC
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
Network	Ethernet	100 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P
Others	Dimention	W430xD300xH55mm
	IR Controller	Yes
	Power Supply	12V/4A
	Operation Temperature	0°C ~50°C